In the Claims:

Please amend claims 5-8 as follows:

1. (Original) A tire wheel assembly which includes a pneumatic tire, and a wheel provided with a rim fitted with the pneumatic tire, and forms a cavity portion between the pneumatic tire and the rim, wherein:

at least one tube, which has one end thereof closed while having a length of 55% to 110% of a reference length L0 corresponding to one fourth of a cavity resonance wavelength, is provided so as to open to the cavity portion.

2. (Original) A tire wheel assembly, which includes a pneumatic tire, and a wheel provided with a rim fitted with the pneumatic tire, and forms a cavity portion between the pneumatic tire and the rim, wherein:

a plurality of tubes, each of which has one end thereof closed while having a length of 55% to 110% of a reference length L0 corresponding to one fourth of a cavity resonance wavelength, are provided so as to open to the cavity portion; and

opening portions of these tubes are arranged in one arbitrary location on a circumference, or in two locations facing each other across a rotational axis of the tire.

3. (Original) The tire wheel assembly according to claim 2, wherein an angle with respect to the rotational axis of the tire, which defines a range of each of the locations

where the opening portions of the tubes are arranged, is equal to or less than 35 degrees.

- 4. (Original) The tire wheel assembly according to any one of claims 1 to 3, wherein the length of the tube is set at 85% to 105% of the reference length L0.
- 5. (Currently Amended) The tire wheel assembly according to any one of claims 1 to 4 claims 1 to 3, wherein a cross-sectional area of the tube is set at 0.2% to 10% of a cross-sectional area of the cavity portion.
- 6. (Currently Amended)The tire wheel assembly according to any one of claims 1 to 3, wherein an inside of the tube is filled with any one of a porous material and a non-woven fabric which have air permeability.
- 7. (Currently Amended)The tire wheel assembly according to any one of claims 1 to 6 claims 1 to 3, wherein the tube is provided with the pneumatic tire.
- 8. (Currently Amended) The tire wheel assembly according to any one of claims 1 to 3, wherein the tube is provided with the wheel.